

**MATERIAL:**

Extrusions: 6063-T6

Castings: 356-T6

Hardware: 18-8 Stainless Steel

WELDMENTS:

Process: M.I.G.

All NAFCO welders are certified
by the State of Wisconsin

AVAILABLE FINISHES:

Anodized; Bronze, Black or Satin
Painted

OPTIONS:

Tenons to your specifications

Removable cap when drilling for arms

Duplex outlets

Vibration Dampeners

Other options available
by consulting NAFCO

NOTE:

Embedded portion coated with a
rubberized protective undercoating.

*Serving our customers and
the industry with quality
products since 1973.*

Round Straight Direct Burial Aluminum Light Poles

POLE CATALOG NUMBER	EXPOSED HEIGHT	EMBEDDED LENGTH*	WALL THICKNESS	SHAFT SIZE	Max EPA AT: (Allows for 1.3 Gust Factor)				
					80 MPH	90 MPH	100 MPH	110 MPH	120 MPH
4R10CI	10'	3'	.125	4"	9.0	7.4	5.6	4.8	3.7
4R12CI	12'	3'	.125	4"	7.5	5.4	3.9	3.3	2.4
4R14CI	14'	3'	.125	4"	5.7	3.9	2.6	2.1	1.3
4R15CI	15'	3'	.125	4"	4.8	3.3	2.1	1.6	0.8
4R16CI	16'	3'	.125	4"	4.2	2.6	1.6	1.1	-
4R18DI	18'	3'	.188	4"	5.7	3.7	2.3	1.7	1.0
4R20DI	20'	3'	.188	4"	4.2	2.5	1.3	0.7	-
5R20DI	20'	4'	.188	5"	8.1	5.4	3.5	2.8	2.2
6R25DI	25'	4.5'	.188	6"	7.2	4.8	3.5	2.9	2.2
6R30DI	30'	5'	.188	6"	3.4	1.6	-	-	-
6R30EI	30'	5'	.250	6"	6.8	4.3	2.9	2.4	1.7

* Unless otherwise specified

Variations in shaft size and mounting heights listed are available.

All LTL shipped NAFCO 4" poles are wrapped in single wall 200# test corrugated, 5" and 6" are double wall corrugated