

**MATERIAL:**

Extrusions: 6063-T6

Castings: 356-T6

Hardware: 18-8 Stainless Steel

**WELDMENTS:**

Process: M.I.G.

All NAFCO welders are certified  
by the State of Wisconsin

**AVAILABLE FINISHES:**

Anodized; Bronze, Black or Satin  
Painted

**OPTIONS:**

Tenons to your specifications

Removable cap when drilling for arms

Duplex outlets

Vibration Dampeners

Other options available  
by consulting NAFCO

**NOTE:**

Embedded portion coated with a  
rubberized protective undercoating.

*Serving our customers and  
the industry with quality  
products since 1973.*

# Square Direct Burial Aluminum Light Poles

POLE CATALOG NUMBER	EXPOSED HEIGHT	EMBEDDED LENGTH*	WALL THICKNESS	SHAFT SIZE	Max EPA AT: (Allows for 1.3 Gust Factor)				
					80 MPH	90 MPH	100 MPH	110 MPH	120 MPH
4S10CI	10'	3'	.125	4"	13.4	10.2	7.9	6.8	5.4
4S12CI	12'	3'	.125	4"	10.4	7.7	5.7	4.8	3.7
4S14CI	14'	3'	.125	4"	8.1	5.8	4.1	3.4	2.3
4S15CI	15'	3'	.125	4"	7.1	4.9	3.4	2.7	1.7
4S16CI	16'	3'	.125	4"	6.2	4.2	2.7	2.1	1.2
4S18DI	18'	3'	.188	4"	8.2	5.7	3.8	3.0	1.9
4S20DI	20'	3'	.188	4"	6.2	4.0	2.4	1.7	0.7
5S20DI	20'	4'	.188	5"	11.4	7.8	5.1	4.0	2.3
5S25DI	25'	4'	.188	5"	5.6	2.8	0.8	-	-
6S25EI	25'	4.5'	.250	6"	15.9	10.5	6.6	4.9	2.5

\* Unless otherwise specified

Variations in shaft size and mounting heights listed are available.

All LTL shipped NAFCO 4" poles are wrapped in single wall 200# test corrugated, 5" and 6" are double wall corrugated

Dimensions and Specifications subject to change without notice.